



IEEE 802 Network Information

	Open	Secure (WPA)
SSID	VeriLAN	VeriLAN.1x
Default Gateway	172.16.0.15	172.16.16.15
Subnet Mask	255.255.240.0	255.255.240.0
DNS Servers	172.16.0.10 172.16.0.11	172.16.16.10 172.16.16.11
Mail Relay	smtp.events.ieee.org	smtp.events.ieee.org
Domain Suffix	events.ieee.org	events.ieee.org

Additional and updated network support information, including instructions for connecting to the VeriLAN.1x network, can be found on-site at:

<http://newton.events.ieee.org/networksupport/>

- Set your network configuration to “DHCP” or “Automatic Configuration”
- There is not static IP address range available. If you require a static address, please see the Verilan staff at the network helpdesk.
- If you have any issues with connecting to the network or accessing resources, please see the Verilan staff at the network helpdesk.

WPA: The VeriLAN.1x network uses the following protocols:

- WPA/WPA2 (enterprise, *not* PSK)
- TKIP or AES
- EAP/PEAP
- MSCHAP v2
- Username and Password are: IEEE
- There is no Login Domain (if you are prompted, leave this field blank)

If you need additional assistance, please visit the Verilan helpdesk.

NOTE: DO NOT run a DHCP server, Internet Connection Sharing (ICS) or connect any devices that would disrupt network services. Disruptive systems will be blocked from the network and can only be reconnected with the assistance of Verilan engineers.